Theoretical and Applied Fracture Mechanics 15 (1991) 277
Elsevier

Author index

Volume 15 (1991)

Astiz, M.A., see J. Toribio (1) 85–97

Blom, A.F., see R.G. Chermahini (3) 267–276
Bonsang, F., see J.W. Provan (2) 115–129
Branco, C.M., see J.M. Ferreira (2) 131–142
Bukharin, O.A. and L.V. Nikitin, Slow crack growth in viscoelastic solids (3) 199–206
Bulloch, J.H. and I. Schwartz, Fatigue crack extension behaviour in porous plasma spray 80%Ni-20%Cr material: The influence of *R*-ratio (2) 143–154

Cartwright, D.J., see M. Utukuri (3) 257–266
Chai, L. and L.R. Dharani, Analysis of elastic crack bridging in ceramic matrix composites (1) 105–112
Chao, C.K., see G.C. Sih (1) 35–61
Chermahini, R.G. and A.F. Blom, Variation of crack-opening stresses in three-dimensions: finite thickness plate (3) 267–276
Chue, C.H. and Y.D. Wei, Failure initiation sites and instability of structural components with localized energy density (2) 163–177

Dharani, L.R., see L. Chai (1) 105–112

Fabrikant, V.I., Non-axisymmetric normal load on an annular crack (3) 229–236
Ferreira, J.M. and C.M. Branco, Influence of fillet weld joint geometry on fatigue crack growth (2) 131–142
Fett, T., Stress intensity factors for edge crack subjected to mixed mode four-point bending (1) 99–104
Fuentes Pérez, M., see A.M. Meizoso (2) 179–190

Glinka, G., see G. Shen (3) 237–245, 247–255
Guha, B., Fatigue crack growth behaviour of welded cruciform joints (2) 155–162

Hecker, F.W., see J.T. Pindera (1) 11–33
Horiguchi, K., see Y. Shindo (3) 207–217

Jablonski, D.A., see Y.H. Tang (1) 1–9

Lin, S.Y., see G.C. Sih (1) 35–61
Liu, C.H., see G.C. Sih (1) 35–61

Martínez Esnaola, J.M., see A.M. Meizoso (2) 179–190
Meizoso, A.M., J.M. Martínez Esnaola and M. Fuentes Pérez, Approximate crack growth estimate of railway wheel influenced by normal and shear action (2) 179–190

Nikitin, L.V., see O.A. Bukharin (3) 199–206

Ong, C.L. and S.B. Shen, Repair of F-104 aircraft nosedome by composite patching (1) 75–83
Orringer, O., see Y.H. Tang (1) 1–9

Perlman, A.B., see Y.H. Tang (1) 1–9
Pindera, J.T., F.W. Hecker and B. Wen, Testing theoretical bases of caustic methods in fracture mechanics and stress analysis (1) 11–33
Powell, A., see J.W. Provan (2) 115–129
Provan, J.W., F. Bonsang, K. Rezai and A. Powell, A combined fatigue crack initiation and propagation specimen—its initial development (2) 115–129

Rezai, K., see J.W. Provan (2) 115–129

Sanchez-Galvez, V., see J. Toribio (1) 85–97
Schwartz, I., see J.H. Bulloch (2) 143–154
Shen, G. and G. Glinka, Determination of weight functions from reference stress intensity factors (3) 237–245
Shen, G. and G. Glinka, Weight functions for a surface semi-elliptical crack in a finite thickness plate (3) 247–255
Shen, S.B., see C.L. Ong (1) 75–83
Shindo, Y. and K. Horiguchi, Dynamic bending of cracked soft ferromagnetic plate in uniform magnetic field (3) 207–217
Sih, G.C., C.K. Chao, C.H. Liu and S.Y. Lin, Deep drawing of plastically and incrementally deformed circular cylindrical cup (1) 35–61

Tang, Y.H., A.B. Perlman, O. Orringer and D.A. Jablonski, Comparison of two crack growth rate models with laboratory spectrum and field tests on rail steel (1) 1–9
Toribio, J., V. Sanchez-Galvez and M.A. Astiz, Stress intensification in cracked shank of tightened bolt (1) 85–97

Utukuri, M. and D.J. Cartwright, Stress intensity factors for a crack near finite boundaries in multiply stiffened sheets (3) 257–266

Wei, Y.D., see C.H. Chue (2) 163–177
Wen, B., see J.T. Pindera (1) 11–33
Wojcik, R., Direction of crack growth initiation in roller contact: strain energy density criterion (2) 191–198
Wu, Y.-E., see W.-N. Yeh (1) 63–74

Yeh, W.-N. and Y.-E. Wu, Enhancement of buckling characteristics for sandwich structure with fiber reinforced composite skins and core made of aluminum honeycomb and polyurethane foam (1) 63–74

Zhang, C., Dynamic stress intensity factors for periodically spaced collinear antiplane shear cracks between dissimilar media (3) 219–227